

SMPTE Assemblies

*Good,
Better & Best*

GOOD ■ BETTER ■ BEST ■



FIBER ASSEMBLIES

Features / Application	Bend Radius	Flexibility	Crush / Tensile Strength	Environmental Characteristics	Price
Mobile truck & outdoor deployment	55.2mm / 2.17in	Mid	Crush Strength 1500N / cm Tensile Strength 700N	Polyurethane	\$\$\$
Studio use & rack patching	60mm / 2.5in	High	Tensile Strength 600N	Thermoplastic Elastomer	\$\$
Outdoor deployment & high foot traffic indoor use	55.2mm / 2.17in	Mid	TBA	Flexible Thermoplastic	\$\$\$
Tactical - harsh environments & high foot traffic	51mm / 2in	Low	TBA	Polyurethane	\$\$\$\$
Lightweight design & high flexibility	46.8mm / 1.84in	High	TBA	Polyethylene	\$\$\$
Most flexible and fully LEMO compatible	55.2mm / 2.17in	Mid	2000N / cm	Polyurethane	\$\$

HF-FUWPUW - M
Mobile Cable - TV-OM-AMS

HF-FUWPUW - S
Studio Cable - C96040

HF-FUWPUW - G
Gepco Cable - GEP-HDC920

HF-FUWPUW - T
Tactical Cable - C-008HBAA5KM

HF-FUWPUW - 7
7mm Cable - AVBSMPTE7MMK

HF-FCFAFCMA
Canare Indoor / Outdoor Cable
LF-2SM9T-CUT